



Steel quality
 Steel: s355 + hot-dip galvanized acc. EN ISO 1461
 Threaded rods: 8.8 FZV

Performance
 Max vertical load equipment per bracket: 60kg
 Max horizontal load antenna front per bracket incl safety factor: 2,4kN
 Max wind load area antenna front per bracket incl form factor (C x A): 0,8m²
 Max horizontal load antenna side per bracket incl safety factor: 1,5kN
 Max wind load area antenna side per bracket incl form factor (C x A): 0,5m²
 Max installation height: 70meter
 Terrain classification: TC1
 Reference wind speed: 27m/s
 M8 nut tightening torque: 24Nm
 M8 2nd nut tightening torque: 24Nm
 M10 nut tightening torque: 30Nm
 M10 2nd nut tightening torque: 47Nm

Can be mounted upside down.

Installation and maintenance guides are available on our website www.telecomsteel.com

Basis for structural design is according to EN 1990:2007 and Danish National Annex DS/EN 1990/NA.
 Manufacturing of the structure is carried out in accordance with Execution Class EXC2 as per EN 1090-1+A1:2012 and EN 1090-2:2018.
 Governing environmental loading is assessed as wind load, and actions on structures are determined according to EN 1991-1-4 and Danish National Annex DS/EN 1991-1-4/NA.
 CE marking is performed in accordance with the Construction Products Regulation (CPR).



Item numbers			
Size	Without adaptor	XM-XH adaptor	5G adaptor
Ø30-Ø114,3mm	40093	40094	40095

Designed by AndersPedersen	Checked by	Approved by	Date	Date 02-02-2026
TELECOMSTEEL DANISH DESIGN & QUALITY		AO single		
40093	Revision G	Sheet 1 / 1		